



HYDRAULIC PLATE COMPACTORS



A FABRIWELD COMPANY

Model Number	Operating Weight: Lbs. (KG)	Plate Dimension: In. (MM)	Vibration Frequency RPM/Min.	Oil Flow: GPM (LPM)	Operating Pressure: PSI (BAR)	Impulse Force: Ton (Tonne)	Carrier Weight: Lbs. (Tonne)
AC 410	772 (350)	35 X 22 (900 X 550)	2,000	12-22 (45-85)	1,450-1,885 (100-130)	4.5 (4)	8,500-22,000 (4-10)
AC 1216	1,543 (700)	46 X 28 (1,160 X 700)	2,000	22-28 (85-105)	1,450-2,175 (100-150)	18 (16.5)	26,500-35,500 (12-16)
AC 1725	2,205 (1,000)	53 X 35 (1,350 X 900)	2,200	32-45 (120-170)	2,175-2,900 (150-200)	12 (11)	39,500-53,000 (18-24)
AC 3040	2,886 (1,300)	59 X 39 (1,500 X 1,000)	2,200	32-45 (120-170)	2,175-2,900 (150-200)	16.5 (15)	66,000-88,000 (30-40)

Greater vibration forces generate stress waves in granular or loose soil material, bringing air to the surface and packing the particles closer together.

Greater impulse action works with the carrier's downward forces to compact cohesive clay-type soils.

The results is a faster, safer, more efficient compaction than other carrier attachments as well as walk-behind plate compactors, rollers, jumping jacks and other machines.



A FABRIWELD COMPANY